

COMMANDER VFD

FW2308 0824
Replaces 0624



DESIGNED TO OPERATE ALL BRANDS AND ALL MOTORS

COMMANDER 2

COMMANDER 3

MODEL #	CMDR2	CMDR3
HP	1/2 to 1-1/2 HP	1/2 to 2 HP
MOTOR TYPE	2-wire 4" submersible motors Above ground motors	3-wire 4" submersible motors Above ground motors
OUTPUT PHASE	Single phase	Single / Three phase
MAX OUTPUT CURRENT	13.1	13.2 Single phase / 8.8 Three phase
INPUT VOLTAGE	230 +/- 10% VAC	
PRESSURE SETTING	25-80 PSI using pressure sensor 10-90% of range using 0-100 PSI transducer	
AMBIENT TEMPERATURE	20° C (-4° F) to 50° C (122° F)	

Other questions? Let's talk.

800.584.8089 or visit FlintandWalling.com to locate a distributor near you.

Flint & Walling • 95 North Oak Street • Kendallville, In 46755 • FlintandWalling.com

© 2024 Flint & Walling, Inc. All rights reserved. Flint and Walling Inc. asserts trademark and copyright rights in the Flint & Walling logo.



INSIDE THE COMMANDER VFD

PREMIUM ENCLOSURE

- Composite enclosure for quiet operation
- Hinged cover for easy access
- Side mounted ventilation
- Full size cooling fan for maximum air flow and temperature control
- NEMA 3R enclosure with premium heatsink

EASY TO USE COMPONENTS

- Drive status indicator lights
- Settings adjustment DIP switches with large easy to read diagram
- Convenient dial for precise underload sensitivity and pressure adjustment
- Compatible with both pressure transducer and switch
- Quality terminal blocks with spacious wiring area
- Includes 0-100 PSI transducer with 16.4ft cable

